

H22V

ATM

MULTI-FUNCTION CASH DISPENSER













- Self-developed cash processing module
- Outstanding capacity and reliability
- Advanced and secure solution
- Easy deployment and maintenance




H22V

ATM

MULTI-FUNCTION CASH DISPENSER

 Controlling Unit	Intel H61/H81/Q87, support Core i3/i5/i7 CPU, 256Gb SSD, Max. 32GB memory, DVD-RW Windows® 7/10/11 TPM2.0
 Display	19" color vandal-resistive consumer display Multi-touch screen Privacy filter
 Value-added Features	Ready for additional non-cash transactions support (opt.): KYC Cardless transaction Payment/top-up service Couponing service Instant card issuance service eBank access Remote teller assistance
 Card Reader	Motorized card reader DIP card reader (opt.) Contactless smart card reader/writer (opt.) EMV Level 1 Anti-skimming design Card return on power failure (opt.) Retract card capacity: max 30 cards (opt.)
 Banknote Processing Unit	High-speed bulk dispenser: Dispensing speed: 7 notes per second Max. 60 notes per transaction Up to 4 cassettes Cassette capacity: max. 3,500 notes Reject/Retract capacity: max. 300 notes
 Keypad	4*4 metal encryption PIN pad Dust proof/water proof/vandal resistant PCI5.x compliant EMV certified
 Receipt Printer	Graphic thermal receipt printer Capture and retract capability (opt.)
 Security ¹	Electronic lock Mechanical key lock UL & CEN Safe PCI 5.x compliant EPP PIN Pad shield Customer awareness mirror EMV Level 1 certified card reader Anti-Skimming electromagnetic interference device Anti-jackpotting features
 Maintenance	10" LCD service panel with touch screen on TTW type Front, rear and side access
 Environment	Indoor: 0°C~40°C (32°F~104°F) Outdoor: -35°C~50°C (-31°F~122°F) (with optional heating unit) Relative humidity: 20% to 95% (non-condensing)

¹ Additional security options available upon request.

	H22V	H22VL
Type	Through-the-Wall	Lobby
 Access	Rear	Front
 Weight	510kg (UL safe)	500kg (UL safe)
 UL Safe Dimension	Height	1716mm
	Width	620mm
	Depth	1026mm
		1489mm
		476mm
		855mm

