

NTM-G68












NewNote Teller Machine



- Virtual Teller Machine
- Banking Transformation
- Self-Service and Processes Automation
- High performance cash recycling technology
- Bank notes, coins and bank cheques processing
- Premier Security and Biometrics
- 24/7 availability to banking services
- High capacity and proven performance

NTM-G68

NewNote Teller Machine

 Controlling Unit	Intel H61/H81/Q87, support Core i3/i5/i7 CPU, 256Gb SSD, Max. 32GB memory, DVD-RW Windows® 7/10/11 TPM2.0
 Customer Interface	Portrait display 27" multitouch w/ privacy filter Video conference camera (opt.)
 Card Reader	ID Card/Passport Scanner QR Code/Barcode Scanner
	DIP Card Reader Contactless Card Reader
	Deposit & dispensing speed: 12 notes per second
	Recycling denomination support: Max. 8
 Banknote Processing Unit	Maximum of 5 cassettes: 4 Dual-Recycling Cassettes 1 Recycling Cassette
	Cassette capacity: Recycling Cassettes max. 2,850 notes Dual-Recycling Cassette max. 1,800 notes (600/1,200) (The Dual-Recycling Cassette has two recycling compartments inside, which can accept 600 and 1,200 notes respectively.)
	Escrow capacity: 200 notes
 Coins Processing Unit	Deposit: Tilt tray capacity 200 coins Depositing speed 600 coins/min Coin authenticity validation Foreign object detection
	Dispense: 4 hoppers capacity of ~1000 coins per hopper (depend on coin size) dispensing speed – 3~5 coins/sec
 Cheque Deposit Module	Bulk Deposit (up to 30 cheques per bundle)
 Receipt Printer	Graphic thermal receipt printer Capture and retract capability (opt.)
 Security ¹	Electronic lock Mechanical key lock UL & CEN Safe PCI 5.x compliant EPP PIN Pad shield Customer awareness mirror EMV Level 1 certified card reader Anti-Skimming electromagnetic interference device Anti-jackpotting features Pinhole camera
 Environment	Indoor: 0°C~40°C (32°F~104°F)
	Relative humidity: 20% to 95% (40°C, non-condensing)
	Metal & Paint with saline resistance
 Access	Front access
 Weight	Main Cabinet: 520kg (UL safe)
	SideCar: 220kg
 Dimensions	1043mm x 1793mm x 1075mm

¹ Additional security options available upon request.



+ 351 210 401 500
info@newnote.pt
www.newnote.pt