

P180

RETAIL PIN PAD



Contactless



EMV



PCI PTS



Linux



Wi-Fi

- Customer-facing pinpad integrated with ECR
- 3.5-inch capacitive touchscreen
- 2MP Customer-facing Camera
- PCI PTS 6.x

P180

RETAIL PIN PAD

OS Operating System	Linux
Processor	Dual-core Cortex A7, 1GHz + Secure Processor
Memory	256MB RAM, 256MB FLASH Micro SD (up to 32GB)
Display	3.5-inch TFT full color LCD display, resolution of 320 x 480 Capacitive touchscreen, support electronic signature
Magnetic Card Reader	Triple track, bi-directional, conforming to ISO 7810/7811/7813
Smart Card Reader	EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1
Contactless Card Reader	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare, Felica, HCE
Camera	2M pixels
Audio	Speaker 1.5W (optional)
Keypad	10 x numeric keys Back light 5 x function keys (Cancel(include ON/OFF), Enter backspace, *, #)
Communication	RS232 USB Devises Ethernet 10/100M WIFI 2.4GHz/5GHz (both optional)
Accessories	Kensington lock Privacy Shield Rotatable mount Customizable multifunction cable (all optional)
Card Slots	2 x SAM
Power	Input: AC 100~240V Output: DC 5V/2A PUSB (optional)
Dimensions	163mm (L) x 74mm (W) x 31mm (H) Without Privacy Shield 163mm (L) x 74mm (W) x 46mm (H) With Privacy Shield
Weight	NET weight 252g. Gross weight 713g
Environment	Operating temperature: -10°C~50°C (14°F~122°F) Storage temperature: -20°C~70°C (-4°F~158°F) Relative humidity: 5%~95% (Non-condensing)
Certifications	PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American Expresspay, Discover D-PAS, AMEX, QuickPass, TQM, RoHS, CE, ANATEL, ABECS, FCC, JCB, UPTS 3.0

