

P2600

ATM


CASH DEPOSIT MACHINE




- Efficient Application
- Affordable Expense
- Reliable Quality & Durability
- Compact Design
- Convenient & Secure Transportation

P2600


ATM
CASH DEPOSIT MACHINE

 Controlling Unit


Intel H61/H81/Q87, support Core i3/i5/i7 CPU, 256Gb SSD, Max. 32GB memory, DVD-RW | Windows® 7/10/11 | TPM2.0

 Display


15" TFT color LCD with touch screen | Privacy filter | Advertisement display light panel (opt.)

 Communication


Standard TCP-IP connection

 Card Reader


Motorized card reader | DIP card reader (opt.) | Contactless smart card reader/writer (opt.) | EMV Level 1 and Level 2 compliant | Anti-skimming design | Card return on power failure (opt.) | Retract card capacity: max 30 cards (opt.)

 Banknote Processing Unit

High-speed bulk dispenser: Dispensing speed: 7 notes per second | Max. 60 notes per transaction | Up to 4 cassettes | Cassette capacity: max. 3,500 notes
Reject/Retract capacity: max. 300 notes

 Keypad


4*4 metal encryption PIN pad | Dust proof/water proof/vandal resistant | PCI5.x compliant | EMV certified

 Receipt Printer


80mm 203DPI graphical thermal printer | Capture and retract capability

 Security¹

Electronic lock | Mechanical key lock | UL & CEN Safe | PCI 5.x compliant EPP | PIN Pad shield | Customer awareness mirror | EMV Level 1 certified card reader | Anti-Skimming electromagnetic interference device | Anti-jackpotting features

 Maintenance

10.4" LCD service panel with touch screen (available on rear access model)
Front, rear and side access

 Environment

Indoor: 0°C ~ 40°C (32°F ~ 104°F)

Outdoor: -10°C ~ 50°C (14°F ~ 122°F) (with optional heating unit)

Relative humidity: 20% to 95% (non-condensing)

¹ Additional security options available upon request.

		H22N	H22NL
Type		Through-the-Wall	Lobby
 Access		Rear	Front
 Weight		533kg	524kg
 Dimension	Height	1646mm	1673mm
	Width	490mm	490mm
	Depth	1080mm	865mm



+ 351 210 401 500
info@newnote.pt
www.newnote.pt