

# P2600S

ATM











CASH DEPOSIT MACHINE



- Efficient Application
- Affordable Expense
- Reliable Quality & Durability
- Compact Design
- Convenient & Secure Transportation

# P2600S

ATM  
CASH DEPOSIT MACHINE

 Controlling Unit	Intel H61/H81/Q87,support Core i3/i5/i7 CPU, 256Gb SSD, Max. 32GB memory, DVD-RW   Windows® 7/10/11   TPM2.0
 Display	15" TFT color LCD with touch screen   Privacy filter   Advertisement display light panel (opt.)
 Communication	Standard TCP-IP connection
 Card Reader	Motorized card reader   DIP card reader (opt.)   Contactless smart card reader/writer (opt.)   EMV Level 1 and Level 2 compliant   Anti-skimming design   Card return on power failure (opt.)   Retract card capacity: max 30 cards (opt.)
 Banknote Processing Unit	High-speed bulk dispenser: Dispensing speed: 7 notes per second   Max. 60 notes per transaction   Up to 4 cassettes   Cassette capacity: max. 3,500 notes Reject/Retract capacity: max. 300 notes
 Keypad	4*4 metal encryption PIN pad   Dust proof/water proof/vandal resistant   PCI5.x compliant   EMV certified
 Receipt Printer	80mm 203DPI graphical thermal printer   Capture and retract capability
 Security <sup>1</sup>	Electronic lock   Mechanical key lock   UL & CEN Safe   PCI 5.x compliant EPP   PIN Pad shield   Customer awareness mirror   EMV Level 1 certified card reader   Anti-Skimming electromagnetic interference device   Anti-jackpotting features
 Maintenance	10.4" LCD service panel with touch screen (available on rear access model) Front, rear and side access
 Environment	Indoor: 0°C ~ 40°C (32°F ~ 104°F) Outdoor: -10°C ~ 50°C (14°F ~ 122°F) (with optional heating unit) Relative humidity: 20%to 95% (non-condensing)

<sup>1</sup> Additional security options available upon request.

		H22N	H22NL
Type		Through-the-Wall	Lobby
 Access		Rear	Front
 Weight		533kg	524kg
 Dimension	Height	1646mm	1673mm
	Width	490mm	490mm
	Depth	1080mm	865mm



+ 351 210 401 500  
info@newnote.pt  
www.newnote.pt